



## PRODUCT SPECIFICATIONS

### PRODUCT FORM

**Standard Thickness:** 5/16" (8mm)

**Weight:** 1.55 lbs./sq.ft.

**Standard Width:** 48"

**Standard Colors:** Brick Red, Green, Light Gray

**Custom Colors, Thicknesses and Widths:** Available upon request (minimums apply). Allow extra lead time.

### PRODUCT PERFORMANCE DATA

<b>Density</b>	ASTM D3676	Cushion Layer-45 lbs./cu.ft., Wear Layer-79lbs./cu.ft.
<b>Hardness</b>	ASTM D2240 (Shore A)	55
<b>Force Reduction</b>	DIN 18032-2	21%
<b>Ball Rebound</b>	DIN 18032-2	98%
<b>Vertical Deformation</b>	DIN 18032-2	1.31
<b>Sliding Behavior</b>	DIN 18032-2	Dry -1.07, Wet -.74
<b>Residual Indentation</b>	ASTM F970	0.006 at 250 psi
<b>Abrasion Resistance</b>	ASTM F1344 1000 cycles	0.73 grams loss



**KO101 Brick Red**



**KO102 Green**



**KO103 Light Gray**



Sports & Fitness Flooring



Running Surfaces



Turf Underlayment



Sound Absorption