EVERLAY ® PROTECTION

FIBERGLASS-REINFORCED UNDERLAYMENT

EVERLAY® PROTECTION

Prefabricated resilient underlayment for installation with Mondo indoor sport products to increase sound and shock absorption.

MONDO®

EVERLAY® PROTECTION

FIBERGLASS-REINFORCED UNDERLAYMENT

SPECIFICATIONS

Texture:	Smooth
Thickness:	3/16" (4.7 mm)
Roll Width:	6' 6" (2 m)
Roll Length:	65' 7" (20 m)*

* Average length from production

EVERLAY® PROTECTION

Everlay® Protection is a 4.7 mm stabilizing underlayment for indoor installation with Mondo sports flooring products. It is composed of expanded PVC and reinforced with fiberglass. Its underside has a series of small stems in expanded resin to allow air circulation.

BENEFITS OF EVERLAY® PROTECTION UNDERLAYMENT

- Eliminates abatement cost
- Minimizes construction delays
- Increases sound absorption
- Increases shock absorption
- Does not form a thermal barrier when radiant heating is used
- Allows for temporary installations with easy removal after useful life

SIMPLIFIED INSTALLATION

Reduced installation time and delays associated with substrate preparation. The Everlay® Protection underlayment can be installed without adhesive onto a suitably prepared surface. It will provide a continuous base with excellent resistance to moisture onto which the new flooring can be installed.

Step 1

Unroll Everlay® onto the subfloor, placing the rolls next to each other and tape the seams.

Step 2

Spread the recommended adhesive onto the surface of Everlay®.

Step 3

Glue on the top layer of flooring.

Printed in Canada - Revised 11/2017

RFS SPORTS FLOORING & LOCKERS

RFS SPORTS • 375 COLUMBIA MEMORIAL PKWY • KEMAH, TX 77565
281.334.6800 • WWW.TEAMRFS.COM • INFO@TEAMRFS.COM